

Trunk Protector

TESTED PRODUCT. GUARANTEED EFFICIENCY

UNE-EN ISO 14067 Certification: Our products have up to 41% less carbon footprint compared to products imported.



FEATURES

- Material: 100% Polypropylene Double-Layer Anti-weed Non woven with UV protection.
- Weight: 60 and 110 gsm
- Mechanically and chemically resistant.
- Breathable.
- Dimensions: according to your needs. Adaptation to all kind of crops.
- Opened or with the possibility of highly-resistant side closure.
- Possibility of printed customization of logos and corporate images.
- Other treatments and colours: upon request.
- UV radiation resistance: with the possibility of increased UV additivation according to your needs.
- Our Double-layer Anti-weed material has the CAAE certificate on conformity as a sustainable raw and compatible with organic farming.



BENEFITS

We offer an optimal and reliable solution to maximize the yield and quality of your crops. At the same time, we ensure biological protection and thermal control of crops, with an environmentally friendly and compatible with organic farming solution.

- Protection of crops from solar radiation and adverse weather conditions.
- Customized manufacturing according to the needs of each type of crop.
- Protection of the plant from damage by rabbits and other wildlife.
- Good air permeability and plant transpiration.
- Increased plant comfort.
- Our flexible fabric provides the perfect protection for plants.
- In subtropical crops, it prevents the proliferation of aerial fungus.
- Prevention of the growth of adventitious buds or shoots around the trunk.
- Easy to handle and place: designed for quick and easy installation.
- 100% recyclable and low landscape impact.

APPLICATION

The black layer on the inside considerably reduces the growth of adventitious buds. The white layer on the outside provides a reflection of sunlight and heat, giving control and uniformity temperatures, and preventing the plant from dying due to excess heat.

DURABILITY AND STORAGE

- It maintains more than 50% of its mechanical properties after 5 years subjected to high solar radiation exposure (accelerated aging chamber test).
- It must be stored in a dry environment, at a temperature below 50°C and protected from UV radiation. In unsuitable conditions, degradation processes may begin.

COLOURS



WHI 01 BLK 01

*Other colours on request

100% CERTIFIED QUALITY



DNT Non Woven Fabrics S.A.

www.dntagro.es

